

[Home \(https://www.liugong.com/en\)](https://www.liugong.com/en) | [Product](#) | [Scissor Lifts \(https://www.liugong.com/en/aerial_work_platforms\)](https://www.liugong.com/en/aerial_work_platforms) | LS0808H

[Product Features](#)

[Applicable-Industry](#)

LS0808H

- **Security And Intelligence:**Intelligent cc personnel safety;Intelligent charging sys
- **Easy To Control:**Drivable at full height t pocket, easy to load, unload and transp
- **Maintenance Friendly:**Self-lubricating : troubleshooting.



Max.Working Height: 10 m

Rated Load on Working Platform: 230 kg

Overall Length/Width: 2.48*0.81 m

(<http://service.weibo.com/share/share.php?url=https://www.liugong.com:443/en/product/ls0808h-2/&title=Security And Intelligence:Intelligent control system, real-time monitoring of equipment status;Multi...>)

LS0808H

Metric U.S

[Product Features](#)

[Specifications](#)

Product Features

[Compare product](#)



Specifications

LS0808H-Mobile Elevating Working Platform (Hydraulic Drive)

Max.Work Height	10 m
Max.Platform Height	8 m
Min.Platform Height	1.22 m
Platform Size (L×W)	2.28×0.81 m
Overall Length	2.49 m
Overall Width	0.844 m
Overall Height (Rails Down)	1.8 m
Max.Gradeability	25 %
Lift Motor	24 V / 3.3 kW
Rated Load on Working Platform	230 kg
Battery	24 V / 200 Ah
Charger	24 V / 30 A
Total Weight	2200 kg

[Download Brochure 1 \(https://www.liugong.com/wp-content/uploads/2024/10/AWP-LS0808H-spec-A4-202410-EN-GB-1.pdf\)](https://www.liugong.com/wp-content/uploads/2024/10/AWP-LS0808H-spec-A4-202410-EN-GB-1.pdf)

[Download Brochure 2 \(https://www.liugong.com/wp-content/uploads/2024/10/AWP-LS0808H-spec-A4-202410-EN-CE-1.pdf\)](https://www.liugong.com/wp-content/uploads/2024/10/AWP-LS0808H-spec-A4-202410-EN-CE-1.pdf)

※For reference only.