

[Home \(https://www.liugong.com/en\)](https://www.liugong.com/en) | [Product](#) | [Scissor Lifts \(https://www.liugong.com/en/aerial_work_platforms\)](https://www.liugong.com/en/aerial_work_platforms) | LS1212E

[Product Features](#) [Applicable-Industry](#)

LS1212E

Secure and Reliable:Complied with GB/CE/AN automatically, which are rust resistant and dur;
Intelligent and Efficient:Automatic display of fa operation; Large ground clearance, maximum
Better Total Cost of Ownership:The generaliza reserve;Maintenance-free AC motors; Low pow improving the life of battery.



Max.Working Height: 14 m

Rated Load on Working Platform: 320 kg

Overall Length/Width: 2.49*1.19m

LS1212E

Metric U.S

[Product Features](#)

[Specifications](#)

Product Features

[Compare product](#)



Specifications

LS1212E-Mobile Elevating Working Platform (Electric Drive)

Max.Work Height	14 m
Max.Platform Height	12 m
Min.Platform Height	2.28 m
Platform Size (L×W)	2.28 x 1.15m
Overall Length	2.49 m
Overall Width	1.19 m
Overall Height (Rails Down)	2.07 m
Max.Gradeability	25 %
Lift Motor	24VAC/3.3k W
Rated Load on Working Platform	320 kg
Battery	24V/225Ah
Charger	24V/30A
Total Weight	3040kg

[Download Brochure 1 \(https://www.liugong.com/wp-content/uploads/2024/05/AWP-LS1212E-spec-A4-202410-EN-GB-1.pdf\)](https://www.liugong.com/wp-content/uploads/2024/05/AWP-LS1212E-spec-A4-202410-EN-GB-1.pdf)

[Download Brochure 2 \(https://www.liugong.com/wp-content/uploads/2024/05/AWP-LS1212E-spec-A4-202410-EN-CE-1.pdf\)](https://www.liugong.com/wp-content/uploads/2024/05/AWP-LS1212E-spec-A4-202410-EN-CE-1.pdf)

※For reference only.